


Leaded Inductors for Class D

插件型数字功放电感

■ PD14B

Features 特点

- Space reduction is realized by 2 in 1 construction.
二合一结构缩小空间
- The optimal design realizes high quality sound and low distortion.
高音质、低失真最佳设计
- Small compact, and DIP type.
小体积，直插类型
- Low radiation noise by magnetically shielded construction
闭合磁路封装，低辐射
- High current, Low resistance.
大电流，低电阻
- Operating temperature : -40°C~+125°C.
工作温度：-40°C~+125°C



Applications 应用

- Suitable as choke for digital amp. Car audio, LCD and PDP TV, 5.1ch Home theater, etc.
适用于数字功放扼流。如汽车音响，LCD 电视和 PDP 电视，5.1 声道家庭影院等

Electrical characteristics 电气特性

Part number 料号	Inductance ① 电感量 $\mu\text{H} \pm 10\%$	DCR ② 直流电阻 $\text{m}\Omega$		SRF ③ 自谐频率 MHz	Isat ④ 直流饱和电流 A typical		Irms ⑤ 温升电流 A typical		
		typ	max.		typical	10% drop	20% drop	30% drop	20°C rise
PD14B-103KL	10	9.9	11	18	12	12.8	13.1	5.8	7.5
PD14B-153KL	15	14	16.5	13	8.2	8.5	9.0	4.7	6.0
PD14B-223KL	22	15.5	18	10	6.5	7	7.3	4.5	5.7
PD14B-333KL	33	19.2	22	7	5	5.2	5.5	3.4	4.8


Remark

- ①Inductance is measured with a LCR meter Agilent 4284A or equivalent.
Test frequency at 100kHz
- ②DC resistance is measured with keithley 580 Milliohm Meter , or equivalent.
Reference ambient temperature 25°C
- ③SRF measured using an Agilent 4395A network analyzer and an Agilent 16193A test fixture.
- ④DC current at 25°C that causes the specified Inductance drop from its value without current.
- ⑤Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
- ⑥Electrical specifications at 25°C



备注

- ①电感量测试采用 Agilent 4284A 数字电桥或同等仪器；
测试频率 100kHz
- ②直流电阻测试采用 keithley 580 毫欧表或同等仪器；
环境温度 25° C
- ③SRF 使用 Agilent 4395A 网络分析仪和 Agilent 16193A 测试夹具测量。
- ④直流电流在 25° C，加载导致指定电感从没有电流的值下降。
- ⑤导致指定温度从 25° C 环境温度上升的电流。此信息仅供参考，不代表绝对最大额定值。
- ⑥25° C 时的电气规格

Dimensions 结构尺寸




Electrical Characteristic Curve 电气特性曲线



■ Packaging Specification - tray: [mm]

包装规格 - 托盘包装: [mm]



Weight 重量: 13.2~13.35g/PCS
Packaging 包装数量: 108 PCS/盘